


REXWAY
CPI



SEAMLESS PIPES & TUBES



SEAMLESS

fire sprinkle pipes

In a fire fighting sprinkler system, one of the main component is the Fire Sprinkler Pipes.

When fire is detected, it help in discharging the water to put out the fire.

We supply our Fire Sprinkle Pipes with the following characteristics :

- REXWAY CPI Seamless Fire Sprinkle Pipes are made of carbon steel in accordance with ASTM A53, A106 standards.
- The wall thickness can be either Schedule 40 or Schedule 80.
- We offer these Fire Sprinkle Pipes in various sizes ranging from ½" to 14" for Schedule 40 and 1" to 8" for Schedule 80. For the finishing you can choose either black varnished coated, or hot dipped galvanised.



Schedule 40 Pipe

Seamless Carbon Steel Pipe Grade B - ASTM A106/A53

Item Code	Nominal Size	OD (mm)	Wall Thickness (mm)	Plain End Weight (Kg/m)	Hydrostatic Test Pressure Grade B
SP40-050	1/2"	21.30	2.77	1.27	17
SP40-075	3/4"	26.70	2.87	1.69	17
SP40-100	1"	33.40	3.38	2.50	17
SP40-125	1-1/4"	42.20	3.56	3.39	17
SP40-150	1-1/2"	48.30	3.68	4.05	17
SP40-200	2"	60.30	3.91	5.44	17
SP40-250	2-1/2"	73.00	5.16	8.63	17
SP40-300	3"	88.90	5.49	11.29	17
SP40-400	4"	114.30	6.02	16.07	15
SP40-500	5"	141.30	6.55	21.77	13
SP40-600	6"	168.30	7.11	28.26	12
SP40-800	8"	219.10	8.18	42.55	11
SP40-1000	10"	273.10	9.27	60.29	10
SP40-1200	12"	323.80	10.31	79.70	9
SP40-1400	14"	355.60	11.13	94.55	9

Schedule 80 Pipe

Seamless Carbon Steel Pipe Grade B - ASTM A106/A53

Item Code	Nominal Size	OD (mm)	Wall Thickness (mm)	Plain End Weight (Kg/m)	Hydrostatic Test Pressure Grade B
SP80-100	1"	33.40	4.55	3.24	17
SP80-125	1-1/4"	42.20	4.85	4.47	17
SP80-150	1-1/2"	48.30	5.08	5.41	17
SP80-200	2"	60.30	5.54	7.48	17
SP80-250	2-1/2"	73.00	7.01	11.41	17
SP80-300	3"	88.90	7.62	15.27	17
SP80-400	4"	114.30	8.56	22.32	19
SP80-500	5"	141.30	9.53	30.97	19
SP80-600	6"	168.30	10.97	42.56	19
SP80-800	8"	219.10	12.70	64.64	17

Pipes from Schedule 40 & Schedule 80 both have the following specifications:

Surface Finishing

- Black Varnished Coated
- Hot Dipped Galvanised

End Finishing


- Plain End (for all sizes)
- Threaded both ends (size 1/2" to 6")

Tolerance

- Outside Diameter: (a) 1-1/2" and below: +/- 1/64 inch (0.4mm)
(b) 2" and above: +/- 1%
- Thickness: +/- 12.5%
- Length: +/- 1/4" (6.35mm)



EX27796





TOGETHER WE ARE BETTER

Insteel (Malaysia) Sdn Bhd (469850-M)

Lot 2-31, Jalan SU 7, Sekyen 26
Off Persiaran Tengku Ampuan
40400 Shah Alam, Selangor Darul Ehsan, Malaysia.
Tel: +603-5192 8003 Fax: +603-5192 1023

www.insteelworld.com

E-mail: info@insteelworld.com



DESCRIPTIVE MATTER AND ILLUSTRATION : (a) All descriptions and illustrations and particulars of weights and dimensions and performance criteria issued by the Company in catalogues, price lists, advertising matter and specifications are by way of general descriptions and approximate only and shall not form part of any contract or give rise to any liability on the part of the Company. (b) It is the policy of the Company to endeavour to develop and improve its products, and accordingly the Company reserves the right to change all specifications without prior notification or public announcement pursuant to such policy, provided that nothing in this clause shall oblige the Purchaser to accept goods which do not reasonably comply with the contract.

COPYRIGHT : All drawings, descriptions and other information submitted by the Company shall remain the property of the Company together with the copyright therein this catalogue.

(*Company* means Insteel (Malaysia) Sdn Bhd)

